



VIKING TRAILERS INTERNATIONAL FZCO DUBAI, U.A.E.

AIRCRAFT PALLET DOLLY MODEL: PD70/TT/FS



APPLICATION

To transport pallets and containers.

Pallet sizes: 125x96, 125x88, 108x88

ULD sizes: 2xLD3, 2xLD1, LD6, LD11

The construction of this dolly combines strength and durability with a light overall weight. One man can maneuver easily.

Designed to tow in train. Materials used are of the highest quality and all components are easily maintained or replaced with minimum effort. No special tools required.

SPECIFICATION

CAPACITY

7,000kg

CHASSIS

Chassis size: 2,670mm (105") x 3,380mm (133")

One piece welded construction with outer walls folded from high grade steel to provide a light weight yet robust structure which is capable of withstanding reasonable collision impacts. Forklift pockets in chassis walls.

TOP DECK

Inverted castor deck with pallets feeding on sides and rear edges. Loading height of 508mm (20"). Total walk over surface (anti-slip). Fork slots in deck for lifting ULD. Lift up stops to retain pallets.

UNDERCARRIAGE

FRONT

Subframe mounted through 850mm ball bearing turntable with 2 sets of twin wheels on rocking axles. Axles have taper bearing hubs with 4 stud fixing.

REAR

Fixed castor assemblies with twin wheels on rocking axles. Axles have taper bearing hubs with 4 stud fixings.

8 wheels fitted with 4.00 x 75 x 8 solid rubber tyres.

BRAKES

Park brake operates on rear wheels and is actuated by raising towbar. Pivoting towbar with 76mm (3") profiled eye. Mounted on narrow edge of dolly. Jaw and pin tow hitch-spring loaded.

FINISH

Hot dip galvanized to ISO 1461.

Day glow paint corners.

Reflective hazard stripes.

OPTIONAL EQUIPMENT

- Extra stop positions for additional ULD sizes.
- Swivel castor steering.
- Towbar can be mounted on wide edge of dolly.
- Painted finish